



# FVP LEAD ACID BATTERY

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: May 1, 2015

Supersedes:

Version:

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Lead Acid Battery  
Classification : Battery wet, filled with acid, electric storage

#### Part Numbers

121R, 121R-6A, 124R, 124R-7A, 12AA, 14A2, 14LA2, 151R, 151R-4A, 16LB, 21, 21-4A, 21R, 21R-4A, 22F, 22F-5A, 22NF, 24, 24-4A, 24-5A, 24-6A, 24-7A, 24F, 24F-4A, 24F-5A, 24F-6A, 24F-7A, 24FHD, 24FXHD, 24FXXHD, 24HD, 24XHD, 24XXHD, 25, 25-5A, 25-6A, 25HD, 26, 26-4A, 26-5A, 26HD, 26R, 26R-4A, 26R-5A, 26RHD, 27, 27-5A, 27-6A, 27-7A, 27F, 27F-5A, 27F-6A, 27F-7A, 27FHD, 27FXHD, 27HD, 27XHD, 31A, 31AHC, 31A-HD, 31ASD, 31AXHD, 31AXXHD, 31T, 31THC, 31T-HD, 31TSD, 31TXHD, 31TXXHD, 34, 34-5A, 34-6A, 34-7A, 34HD, 34SD, 35, 35-5A, 35-6A, 35HD, 40R, 40R-6A, 41, 41-6A, 42, 42-5A, 47/90-6A, 47-90, 48/91-7A, 48-7A, 48-91, 48HD, 49/93-8A, 49-93, 4D, 4D-6A, 4D-7A, 4DHD, 4DLT, 4DLT-7A, 51, 51-4A, 51R, 51R-4A, 58, 58-4A, 58-5A, 58-6A, 58HD, 58R, 58R-4A, 58R-5A, 58R-6A, 58RHD, 58RXHD, 58XHD, 64, 65, 65-7A, 65-8A, 65-9A, 65HD, 65XHD, 70, 70-5A, 70DT, 70DT-4A, 70DT-5A, 70DT-6A, 70DTHD, 70DTXHD, 70HD, 75, 75-5A, 75-6A, 75-7A, 75DT, 75DT-5A, 75DT-6A, 75DT-7A, 75DTHD, 75DTXHD, 75HD, 75XHD, 78, 78-5A, 78-6A, 78-7A, 78-8A, 78DT, 78DT-5A, 78DT-6A, 78DT-7A, 78DT-8A, 78DTHD, 78DTS, 78DTXHD, 78HD, 78SD, 78XHD, 85, 85-7A, 86, 86-6A, 8D, 8D-6A, 8D-7A, 8DBUS, 8DHD, 90, 90-6A, 91, 91-7A, 94R, 94R-7A, 94R-8A, 94RHD, 96R, 96R-6A, C31-10APA, C31-10STA, C31-6APA, C31-6STA, C31-7APA, C31-7STA, C31-8APA, C31-8STA, C31-9APA, C31-9STA, C31HC-7APA, C31HC-7STA, DC24-6A, DC24XHD, DC27-7A, DC31-8A, GC-105, GC110, GC2-105, GC2-125, GC8-890, N200, P22F, P22F-5A, P24, P24-6A, P24F, P24F-6A, P25, P25-6A, P26, P26R, P27F, P27F-8A, P34, P35, P35-6A, P41, P41-7A, P42, P42-5A, P47-90, P4790-6A, P48, P49-93, P4993-8A, P51, P51-5A, P51R, P51R-5A, P58, P65, P75, P75-7A, P75DT, P75DT-6A, P78, P78-7A, P78DT, P86, P86-6A, P91, P94R, SC16CLBFA, SC20HLFA, SM24-6A, SM24-8A, SM24-9A, SM24HD, SM24XHD, SM24XXHD, SM27-8A, SM27-9A, SM27XHD, SM31-8A, U1L, U1L-5A, U1L-6A, U1LHD, U1R, U1R-5A, U1R-6A, U1RHD, 115E41L, 115E41R, 135F51L, 135F51R, 160G51L, 160G51R, 165G51L, 165G51R, 210H52L, 210H52R, 22F-5D, 24-4D, 24-5D, 245H52L, 245H52R, 24-6D, 24-7D, 24F-4D, 24F-5D, 24F-6D, 24F-7D, 25-5D, 25-6D, 27-5D, 27-6D, 27-7D, 27F-5D, 27F-6D, 35-5D, 35-6D, 41-6D, 42-5D, 47/90-6D, 48/91-7D, 49/93-8D, 4D-6D, 4D-7D, 4DHD, 4D-7D, 4DHDS, 4DS, 51-4D, 51R-4D, 65-7D, 65-8D, 65R-7D, 65R-8D, 75-6D, 75-7D, 75DT-6D, 75DT-7D, 78-6D, 78-7D, 78DT-6D, 78DT-7D, 86-6D, 8D-1400, 8D-6D, 8D-7D, 8DHDS, 8DS, 94R-7D, 94R-8D, 95E41L, 95E41R, C31-10APD, C31-10STD, C31-6APD, C31-6STD, C31-7APD, C31-7STD, C31-8APD, C31-8STD, C31-9APD, C31-9STD, M24-500D, M24-560D, M24-5DP, M24-600D, M24-700D, M24-750D, M24-780ST, M24-7DC, M27-1040ST, M27-600D, M27-700D, M27-710D, M27-780ST, M27-7DC, M27-7DP, M27-800D, M31-1235ST, M31-800D, M31-850D, M31-8DP, M31-900D, M31-950D, 3EE, C1, C4, 59, 3ET, 3EH, C2, DC24, DC27, 34R, 16CLB, SM24, 45, DC31, 36R, DC27HD, 8DBUS313, 8DBUS312, SC30LFA, 14AA-2, 8DXHD, 5D, 30H, 79, 101, 124R-60BB, 21-4, 21R-4, 22F-5, 24-4, 24-5, 24-6, 24-7, 24-8, 24F-4, 24F-5, 24F-6, 24F-7, 24F-8, 25-5, 25-6, 26-4, 26-5, 26R-4, 26R-5, 27-5, 27-6, 27-7, 27F-5, 27F-6, 27F-7, 34-5, 34-6, 34-7, 34R-7, 35-5, 35-6, 40R-6, 41-6, 42-5, 47/90-6, 48/91-7, 48-10, 48-8, 49/93-8, 4D-6, 4D-7, 51-4, 51R-4, 58-4, 58-5, 58-6, 58R-4, 58R-5, 58R-6, 65-7, 65-8, 65-9, 70-5, 70-6, 70DT-4, 70DT-5, 70DT-6, 75-5, 75-6, 75-7, 75DT-5, 75DT-6, 75DT-7, 78-5, 78-6, 78-7, 78-8, 78DT-5, 78DT-6, 78DT-7, 78DT-8, 86-6, 8D-6, 8D-7, 8D-8, 94R-7, 94R-8, 94R-9, 96R-6, C31-10AP, C31-10ST, C31-11AP, C31-11ST, C31-6AP, C31-6ST, C31-7AP, C31-7ST, C31-8AP, C31-8ST, C31-9AP, C31-9ST, C31HC-7AP, C31HC-7ST, DC24-3, DC24-4, DC24-5, DC24-6, DC27-5, DC27-6, DC31-8, GC1275WNG, GC2-105WNG, GC2-105WNI, GC2-125WNG, GC2-125WNI, GC2-145WNG, GC2-605WNG, GC8-875WNG, GC8-875WNI, GC8-890WNG, GC8-890WNI, N100, N120, NS40Z, NS40ZL, NS60LS, NS60S, SM24-5, SM24-6, SM24-8, SM24-9, SM27-8, SM27-9, U1L-5, U1L-6, U1L-7, U1R-5, U1R-6, U1R-7, 800476, 800477, GC1275-WNGTRJ, 800522, GC2-105WNGTRJ, GC8-875WNGTRJ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Battery to produce a voltage

#### 1.3. Details of the supplier of the safety data sheet

Factory Motor Parts  
1380 Corporate Center Curve, Suite 200  
Eagan, MN 55121  
1-866-387-3343

#### 1.4. Emergency telephone number

Emergency number : 82-42-620-4332

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Substances and mixtures, which in contact with water, emit flammable gases, categories 2

Acute toxicity (oral, dermal, inhalation) categories 1

Skin corrosion categories 1

Serious eye damage category 1

Carcinogenicity categories 1A

Germ cell mutagenicity categories 2

Reproductive toxicity categories 1A

Specific Target Organ Toxicity - Single exposure categories 1

Specific Target Organ Toxicity - Repeated exposure categories 1

#### 2.2. Label elements

##### GHS-US labeling

1) Pictogram

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



2) GHS Signal word : Danger

3) GHS Hazard statements

H261 In contact with water releases flammable gas

H314 Cause severe skin burns and eye damage

H318 Causes serious eye damage

H330 Fatal if inhaled

H341 Suspected of causing genetic defects

H350 May cause cancer

H360 May damage fertility or the unborn child

H370 Causes damage to organs

H372 Causes damage to organs through prolonged or repeated exposure

4) GHS Precautionary statements

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P223 Do not allow contact with water

P231 + P232 Handle under inert gas. Protect from moisture.

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P264 Wash ... thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection/face protection

P281 Wear protective gloves/protective clothing/eye protection/face protection

P284 [In case of inadequate ventilation] wear respiratory protection

5) GHS First aid measure

P301 + P330 + P331 If SWALLOWED : Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 If ON SKIN(or hair) : Take off immediately all contaminated clothing. Rinse skin with water/shower

P304 + P340 IF INHALED : IF INHALED : Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P307 + P311 Immediately call a POISON CENTER/doctor/...

P308 + P313 IF exposed or concerned : Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor/

P314 Get medical advice/attention if you feel unwell.

P320 Specific treatment is urgent (see ... on this label).

P321 Specific treatment (see ... on this label).

P335 + P334 Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire : Use ... to extinguish.

6) GHS Storage

P402 + P404 Store in a dry place. Store in a closed container.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

7) GHS Disposal

P501 Dispose of contents/container to ... in accordance with local/regional/national/international regulations (to be specified).

## 2.3. Other hazards (which do not result in classification (NFPA))

### ANTIMONY

Health 2

Flammability 2

Reactivity 0

### ARSENIC

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Health	2
Flammability	0
Reactivity	0
<b><u>CALCIUM</u></b>	
Health	3
Flammability	1
Reactivity	2
<b><u>SULFURIC ACID</u></b>	
Health	3
Flammability	0
Reactivity	2
<b><u>LEAD</u></b>	
Health	1
Flammability	0
Reactivity	0
<b><u>TIN</u></b>	
Health	1
Flammability	3
Reactivity	0
<b><u>POLYPROPYLENE</u></b>	
Health	1
Flammability	1
Reactivity	0

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Hazardous Components Specific Chemical Identity (Common Name(s))	OSHA PEL	ACGIH TLV	Range Percent By Weight	Average	*SVHC? (REACH)
Lead, CAS #7439921	0.05 mg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>	48~56	52	No
Sulfuric Acid, CAS #7664939	1.00 mg/m <sup>3</sup>	1.00 mg/m <sup>3</sup>	33~44	39	No
Antimony, CAS #7440360	0.50 mg/m <sup>3</sup>	0.50 mg/m <sup>3</sup>	0-4	<1	No
Arsenic, CAS #7440382	0.01 mg/m <sup>3</sup>	0.01 mg/m <sup>3</sup>	<.01	-	No
Polypropylene, CAS #9003070	-	-	5-8	6	No
Calcium, CAS #7440702	1.0mg/m <sup>3</sup>	1.0 mg/m <sup>3</sup>	<1	<1	No

\* SVHC : Substances of Very High Concern (REACH Regulation in EU)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Contact with internal components if battery is opened, broken or spilled.
First-aid measures after inhalation	: Remove to fresh air and provide medical oxygen/CPR if needed. Obtain medical attention.
First-aid measures after skin contact	: Flush contacted area with large amounts of water for at least 15 minutes. Remove contaminated clothing and obtain
First-aid measures after eye contact	: Immediately flush with water for at least 15minutes, hold eyelids open. obtain medical attention.
First-aid measures after ingestion	: Do not induce vomiting. If conscious drink large amounts of water/milk. Obtain medical attention. Never give anything

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Class ABC, CO2 Halon Auto-Ignition Temperature : Polypropylene 675□

### 5.2. Special hazards arising from the substance or mixture

Hydrogen gas and sulfuric acid vapors are generated upon overcharge and polypropylene case failure. Ventilate charging areas as per ACGIH Industrial Ventilation : A Manual of Recommended Practice and National Fire Code.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1980 Vol.1, P.12, B-9, 10. Hydrogen gas may be flammable or explosive when mixed with air, oxygen, chlorine. Avoid open flames/sparks/other sources of ignition near battery. To avoid risk of fire or explosion, keep sparks or other sources of ignition away from batteries and do not allow metallic materials to simultaneously contact negative and positive terminals of cells and batteries. SULFURIC ACID REACTS VIOLENTLY WITH WATER/ORGANICS.

## 5.3. Advice for firefighters

Firefighting instructions : Lead-acid batteries do not burn or burn with difficulty. Do not use water on fires where molten metal is present. Extinguish fire with agent suitable for surrounding combustible materials. Cool exterior of battery if exposed to fire to prevent rupture. The acid mist and vapors generated by heat or fire are corrosive. Use NIOSH approved self-contained breathing apparatus (SCBA) and full protective equipment operated in positive-pressure mode.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Acid resistant aprons, boots and protective clothing. ANSI approved safety glasses with side shields/face shield recommended. Ventilate enclosed areas.

### 6.2. Environmental precautions

Lead and its compounds and sulfuric acid can pose a severe threat to the environment. Contamination of water, soil, and air should be prevented.

### 6.3. Methods and material for containment and cleaning up

Stop release, if possible. Avoid contact with any spilled material. Contain spill, isolate hazard area, and deny entry. Limit site access to emergency responders. Neutralize with sodium bicarbonate, soda ash, lime or other neutralizing agent. Place battery in suitable container for disposal. Dispose of contaminated material in accordance with applicable local, state and federal regulations. Sodium bicarbonate, soda ash, sand, lime or other neutralizing agent should be kept on-site for spill remediation.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling and storage

Keep away from flames during and immediately after charging. Combustion or overcharging may create or liberate toxic and hazardous gases and liquids including hydrogen, sulfuric acid mist, sulfur dioxide, sulfur trioxide, stibine, arsine and sulfuric acid. Store batteries in cool, dry, well ventilated area. Do not short circuit battery terminals, or remove vent caps during storage or recharging. Protect battery from physical damage.

### 7.2. Other Precautions

GOOD PERSONAL HYGIENE AND WORK PRACTICES ARE MANDATORY. Refrain from eating, drinking or smoking in work areas. Thoroughly wash hands, face, neck, and arms before eating, drinking or smoking. Launder soiled clothing before reuse. Emptied batteries contain hazardous sulfuric acid residue.

## SECTION 8: Exposure controls/personal protection

**Respiratory Protection(Specify Type)** : Acid/gas NIOSH approved respirator is required when the PEL is exceeded or employee experiences respiratory irritation. When exposure levels are unknown or when firefighting, wear a self-contained breathing apparatus with a full face piece operated in a positive pressure mode.

**Ventilation** : Must be provided when charging in an enclosed area. Change air every 15min.

Local Exhaust : When PEL is exceeded.

**Mechanical(General)** : Normal mechanical ventilation recommended for stationary applications.

**Protective Gloves** : Wear rubber or plastic acid resistant gloves with elbow length gauntlet when filling batteries.

**Eye Protection** : ANSI approved safety glasses with side shields/face shield recommended safety goggles.

**Other Protective Clothing or Equipment** : Ventilation as described in the Industrial Ventilation Manual produced by the American Conference of Governmental Industrial Hygienists, shall be provided in areas where exposures are above the PEL or TLV specified by OSHA or other local, state and federal regulations. Acid-resistant rubber or plastic apron, boots and protective clothing. Safety shower and eyewash.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Boiling Point</b>	: Electrolyte Approx. 235°
<b>Specific Gravity</b>	: Electrolyte 1.250-1.320 pH<2
<b>Percent Volatile by Volume</b>	: Not Applicable
<b>Evaporation Rate</b>	: Note Applicable
<b>Reactivity in Water</b>	: Electrolyte - water reactive(1)
<b>Appearance and Odor</b>	: Battery : Polypropylene or hard rubber case, solid. Lead : Gray, metallic, solid Electrolyte : Liquid, colorless, oily fluid; nuisance odor when got or charging battery.
<b>Vapor Pressure</b>	: Electrolyte 1mm Hg @ 145.8°
<b>Melting Point</b>	: Polypropylene <320°

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Vepar Density</b>	: Hydrogen(Air=1) - 0.069 Electrolyte(Air=1) - 3.4 At STP
<b>Solubility in Water</b>	: Electrolyte - 100% Soluble

## SECTION 10: Stability and reactivity

### 10.1. Chemical stability

Stable

### 10.2. Possibility of hazardous reactions

Stable

### 10.3. Conditions to avoid

High temperatures - cases decompose at < 320 °C  
Avoid overcharging and smoking, or sparks near battery surface and rapid overcharge

### 10.4. Incompatible materials

Spark, Open flames, Keep battery case away from strong oxidizers.

### 10.5. Hazardous decomposition products

An explosive hydrogen/oxygen mixture within the battery may occur during charging. Combustion can produce carbon dioxide(CO<sub>2</sub>) and carbon monoxide(CO). Molten metals produce fumes and/or vapor that may be toxic or respiratory irritants.

### 10.6. Hazardous Polymerization

Will Not Occur (Do not overcharge)

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Information on the likely routes of exposure:** The primary routes of exposure to lead are ingestion or inhalation of dust and fumes.

#### ACUTE :

INGESTION/INHALATION : Exposure to lead and its compounds may cause headache, nausea, vomiting, abdominal spasms, fatigue, sleep disturbances, weight loss, anemia, and pain in the legs, arms and joints. Kidney damage, as well as anemia, can occur from acute exposure.

#### CHRONIC :

INHALATION/INGESTION : Prolonged exposure to lead and its compounds may produce many of the symptoms of short-term exposure and may also cause central nervous system damage, gastrointestinal disturbances, anemia, and wrist drop. Symptoms of central nervous system

## SECTION 12: Ecological information

### 12.1. Aquatic and terrestrial ecotoxicity

In most surface water and groundwater, lead forms compounds with anions such as hydroxides, carbonates, sulfates, and phosphates and precipitates out of the water column.

### 12.2. Persistence and degradability

Lead may occur as sorbed ions or surface coatings on sediment mineral particles or may be carried in colloidal particles in surface water.

### 12.3. Bioaccumulative potential

Lead(when in the dissolved phase) is bioaccumulated by plants and animals, both aquatic and terrestrial.

### 12.4. Mobility in soil

Most lead is strongly retained in soil, resulting in little mobility. Lead may be immobilized by ion exchange with hydrous oxides or clays or by chelation with humic or fulvic acids in the soil

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Lead-acid batteries are completely recyclable. Return whole scrap batteries to distributor, manufacturer or lead smelter for recycling. For information on returning batteries to ATLASBX Battery Company for recycling call 82-42-620-4332. For neutralized spills, place residue in acid-resistant containers with sorbent material, sand or earth and dispose of in accordance with local, state and federal regulations for acid and lead compounds. Contact local and/or state environmental officials regarding disposal information.

## SECTION 14: Transport information

U.S. DOT PROPER SHIPPING NAME : Batteries, wet filled with acid  
U.S. DOT HAZARD CLASS : 8  
U.S. DOT ID NUMBER : UN2794  
U.S. DOT PACKING GROUP : None  
U.S. DOT LABEL : Corrosive

IMO PROPER SHIPPING NAME : Batteries, wet, filled with acid  
IMO REGULATION PAGE NUMBER : 8120  
IMO U.N.CLASS : 8  
IMO U.N.NUMBER : UN2794  
IMO PACKING GROUP : None  
IMO LABEL : Corrosive  
IMO VESSEL STOWAGE : A

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IATA PROPER SHIPPING NAME : Batteries, wet filled with acid  
IATA U.N.CLASS : 8  
IATA U.N.NUMBER : UN 2794  
IATA PACKING GROUP : None  
IATA LABEL : Corrosive

## SECTION 15: Regulatory information

<b>U.S Hazardous Under Hazard Communication Standard :</b>	Lead : Yes	Sulfuric Acid : Yes Antimony : Yes Arsenic : Yes
<b>Ingredients Listed on TSCA Inventory :</b>	Yes	
<b>CERCLA Section 304 Hazardous Substances :</b>	Lead : Yes RQ : NA*	Sulfuric Acid : Yes RQ : 1000 Antimony : Yes RQ : 5000 pounds Arsenic : Yes RQ : 1 pound
pounds		
*Reporting not required when diameter of the pieces of solid metal released is equal to or exceeds 100 micrometers.		
<b>EPCRA Section 302 Extremely Hazardous Substance :</b>	Sulfuric acid : Yes	
<b>EPCRA Section 313 Toxic Release Inventory :</b>	Lead : CAS No 7439-92-1	Sulfuric Acid : CAS No 7664-93-9 Antimony : CAS NO 7440-36-0 Arsenic : CAS NO 7440-38-2

## SECTION 16: Other information

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, ATLASBX.,CO.LTD. MAKES NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. ALTHOUGH REASONABLE PRECAUTIONS HAVE BEEN TAKEN IN THE PREPARATION OF THE DATA CONTAINED HEREIN, IT IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION. THIS MATERIAL SAFETY DATA SHEET PROVIDES GUIDELINES FOR THE SAFE HANDLING AND USE OF THIS PRODUCT ; IT DOES NOT AND CANNOT ADVISE ON ALL POSSIBLE SITUATIONS, THEREFORE, YOUR SPECIFIC USE OF THIS PRODUCT SHOULD BE EVALUATED TO DETERMINE IF ADDITIONAL PRECAUTIONS ARE REQUIRED.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.