



The Confident Solution.™

50/50 PREDILUTED ORANGE FORMULA ANTIFREEZE/COOLANT



FVP® 50/50 Prediluted Orange Formula Antifreeze/Coolant may be used in all General Motors vehicles that require DEX-COOL® Coolant. This formula has a diluted blend of premium long-lasting inhibitors to offer protection for up to 5 years or 150,000 miles against temperature extremes and the ravages of rust, corrosion, and premature water pump failure. This extended life protection is best provided when the cooling system is flushed and filled.

* Always consult the owner's manual to determine the specific maintenance and change intervals for the vehicle

* DEX-COOL is a registered trademark of GM Corporation

Product Specifications when used as directed:

- Meets ASTM D 3306, ASTM D 4985
- May be added to conventional antifreeze/coolant
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications

www.FVPparts.com • (866) 387-3343

50/50 PREDILUTED ORANGE FORMULA ANTIFREEZE/COOLANT

Composition by Volume

Antifreeze/Coolant Concentrate
Total Water
Dyes (Orange)

Typical Values

51%
49%
Trace

Properties

Color

Orange

Odor

Characteristic

Ash Content - ASTM D 1119

1.5% max

pH - 50% by Volume Solution - ASTM D 1287

10.0 – 11.0

Reserve Alkalinity - ASTM D 1121

2.4

Specific Gravity at 20/20°C - 50% by Volume Solution - ASTM D 1122

1.064

Freezing Point

50% by Volume Solution - ASTM D 1177

-34°F (-37°C)

Boiling Point†

50% by Volume Solution - ASTM D 1120

227°F (108°C)

Flash Point (Tag Open Cup) 70% by Volume Solution

None

Foam Test - ASTM D 1881

50 ml/2 sec.

Average Net Weight/Gallon at 68°F (20°C)

8.9 lbs.

† Atmospheric pressure