## FVP LUBRICANTS **CONVENTIONAL MOTOR OIL**



FVP Conventional Motor Oils are premium quality hydrotreated, paraffinic lubricating oils with a technologically advanced additive system including detergents, dispersants, viscosity improver, anti-wear and anti-friction agents, oxidation and corrosion inhibitors. FVP Conventional Motor Oils provide excellent protection in colder weather and excellent fuel economy. FVP Conventional Motor Oils exceed U.S. and import car and light truck warranty requirements for all automotive engines currently in use. FVP Conventional Motor Oils meet or exceed ILSAC GF-6A requirements for use in passenger car engines and the American Petroleum Institute (API) SP, SM, SN and SL classifications.

| PRODUCT SIZES |              |  |  |  |  |
|---------------|--------------|--|--|--|--|
| 30W-QT        | 12/ case     |  |  |  |  |
| 30W-55GAL     | 55 gal. drum |  |  |  |  |
| 5W20-QT       | 12/ case     |  |  |  |  |
| 5W20-55GAL    | 55 gal. drum |  |  |  |  |
| 5W30-55GAL    | 55 gal. drum |  |  |  |  |
| 5W30-QT       | 12/ case     |  |  |  |  |
| 10W30-QT      | 12/ case     |  |  |  |  |
| 10W30-55GAL   | 55 gal. drum |  |  |  |  |
| 10W-40- QT    | 12/ case     |  |  |  |  |
| 10W40-55GAL   | 55 gal. drum |  |  |  |  |
|               |              |  |  |  |  |





| SAE GRADE                        | 5W-20           | 5W-30           | 10W-30          | 10W-40          | SAE30           |
|----------------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Viscosity @ 100°C, cS            | 8.0-8.8         | 9.7-11.5        | 9.7-11.7        | 13.0-15.5       | 9.7-11.5        |
| Viscosity Index                  | 140-160         | 145-168         | 125-150         | 130-155         | 105-125         |
| API Gravity                      | 32.78           | 33.01           | 31.51           | 31.74           | 29.97           |
| Pour Point: °C                   | -48 °C          | -48 °C          | -42 °C          | -42 °C          | -33 °C          |
| Color                            | 3 Max           |
| API: RC<br>(Resource Conserving) | YES             | YES             | YES             | NO              | NO              |
| ILSAC GF-6A Certified            | YES             | YES             | YES             | NO              | NO              |
| API Licensed Service             | SP and<br>prior | SP and<br>prior | SP and<br>prior | SP and<br>prior | SN and<br>prior |



## **FACTORYMOTORPARTS**

WE SUPPLY YOUR SUCCESS.