



# FULL STRENGTH MULTI-VEHICLE ANTIFREEZE/COOLANT



**FVP® Full Strength Multi-Vehicle Antifreeze/Coolant** is recommended, compatible, and formulated for use with any antifreeze/coolant in any vehicle with aluminum and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to guard against temperature extremes and ravages of rust, corrosion, and premature water pump failure. FVP® Full Strength Multi-Vehicle Antifreeze/Coolant provides extended life protection for cars and light-duty trucks up to 5 years or 150,000 miles\* when added to any extended life coolant or when flushed and filled according to directions. Available in gallons and 55 gallon drums.

\*- Compatible with other extended life and conventional coolants.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

**Product specifications when used as directed:**

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/coolant of any make and model of automobile and light duty truck on the road, foreign or domestic
- May be added to any color antifreeze/coolant (color may change, but performance will not be affected)
- Protects aluminum and any other engine metals



# FULL STRENGTH MULTI-VEHICLE ANTIFREEZE/COOLANT

## Composition by Volume

Ethylene Glycol	93.8%
Soluble Inhibitors (Anhydrous)	4.2%
Total Water	2.0%
Dyes (Yellow)	Trace

## Properties

<b>Color</b>	Yellow
<b>Odor</b>	Characteristic
<b>Ash Content</b> - ASTM D 1119	1.2% by weight
<b>pH</b> - 50% by Volume Solution - ASTM D 1287	
<b>Reserve Alkalinity</b> - ASTM D 1121	2.0
<b>Specific Gravity</b> at 20/20°C - 50% by Volume Solution - ASTM D 1122	1.0687
<b>Freezing Point</b> - 50% by Volume Solution - ASTM D 1177	-34°F (-37°C)
<b>Boiling Point</b> † - 50% by Volume Solution - ASTM D 1120	226°F (108°C)
<b>Flash Point</b> (Tag Open Cup) 70% by Volume Solution	None
<b>Foam Test</b> - ASTM D 1881	50 ml/1 sec.
<b>Average Net Weight/Gallon</b> at 68°F (20°C)	9.3 lbs.

† Atmospheric pressure