



FULL SYNTHETIC EUROPEAN FORMULA MOTOR OIL



FVP Full Synthetic European Motor Oil is a premium quality motor oil formulated with select synthetic base stocks and proprietary additive technology to deliver long-lasting engine protection, peak operation and meets stringent high-performance European OEM standards. FVP Full Synthetic European Motor Oil provides aggressive resistance to sludge formation and varnish deposits during stop-and-go driving and under severe operating conditions. Through premium synthetic formulation, excellent oxidation stability and low volatility properties reduce oil consumption between services.

FVP Full Synthetic European Motor Oil, available in SAE grade 5W-40, exceeds global new car warranty performance requirements as defined by API classification SN and European standards ACEA A3/B4-10 & A3/B3-10.

Available in quarts and 55 gallon drums

- 5W-40

FULL SYNTHETIC EUROPEAN FORMULA MOTOR OIL

SAE GRADE	5W-40
Density @ 15°C, g/cc ³	.860
CCS Viscosity, cP (mPa•s)	5870 @ -30
Viscosity @ 40°C, cSt	95.0
Viscosity @ 100°C, cSt	13.5
Viscosity Index	170
Pour Point: °C	-18 (-26)
Flash Point: °C	220 (430)
ACEA Performance:	A3/B4-12
API Gravity @ 60°F :	32.9
API Licensed Service:	SN/CF
NOACK Volatility, wt%	<10.0

Recommended for service in turbo-charged & fuel-injected gasoline motors and turbo-charged, inter-cooled, & direct injection diesel engines found in passenger cars, light-trucks, and sport utility vehicles requiring:

- API Licensed Service SN/CF
- ACEA A3/B4-10 & A3/B3-10
- BMW LL-01
- Mercedes Benz 229.3 & 229.5
- Porsche A40
- Volkswagen 501.01, 502.00 & 505.00
- Renault RN0700 & RN0710