

FVP 5 QUART LUBRICANTS FULL SYNTHETIC MOTOR OIL

MAXIMUM ENGINE PROTECTION & PERFORMANCE

FVP Full Synthetic Motor Oils is formulated with higher quality synthetic base oils and premium additive technology to provide exceptional engine protection even under harsh stop-and-go driving conditions, extreme temperatures and heavy loads. It provides outstanding protection for vehicles with direct-injection and turbochargers and those that require a full synthetic motor oil. FVP Full Synthetic Motor engine oils are specifically formulated to meet the latest API and ILSAC requirements of aged oil LSPI protection, increased limits for fuel economy, piston deposits, timing chain wear, & low temperature pumpability, along with a cap on sulfated ash level for gasoline particulate filter compatibility. These engine oils continue to provide excellent protection against sludge, piston cleanliness, engine rust and corrosion for all engine types under severe service or low temperature operation.

Industry and OEM Applications

- API SQ, SP, SN, SN Plus and previous categories
- ILSAC GF-7A, Resource Conserving
- Chrysler MS-6395S
- Meets the requirements for FORD:
 - WSS-M2C960-A1 (5W-20) *
 - WSS-M2C961-A1 (5W-30) *
- Toyota, Honda, Nissan, and Hyundai **

*Backwards compatible with Ford WSS-M2C960-A1 (5W-20), WSS-M2C961-A1 (5W-30) and GM6094M/ GM4718M (obsolete).

**Require ILSAC GF-7 approved oils for service fill. Additional unpublished specifications for factory fill and genuine oils.



SAE GRADE	5W-20	10W-30
Viscosity @ 40°C, cSt	50.47	67.43
Viscosity @ 100°C, cSt	8.986	10.76
Viscosity Index	160	150
Specific Gravity @ 60°F	0.8520	0.8541
Pour Point, °C	-42	-39
Color ASTM	L3.0	L3.0
Cold Crank Simulator, cP	4,426 (-30°C)	4,513 (-25°C)
Flash Point, °C	224	251
TBN, mg KOH/g	7.3	7.2
Noack Volatility, %	10.9	7.1
HTHS, cP	2.6	3.0

PRODUCT SIZES

5W20FS-5QT	4/ case
10W30FS-5QT	4/ case

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™
WE SUPPLY YOUR SUCCESS.®