

# 50/50 PREDILUTED EXTENDED LIFE HEAVY DUTY RED ANTIFREEZE/COOLANT



## 50/50 PREDILUTED FORMULA

FVP® 50/50 Prediluted Extended Life Heavy Duty Antifreeze/Coolant is formulated for all heavy duty diesel trucks. Heavy duty engines on and off road.

### Product specifications when used as directed:

- Advance corrosion protection
- Silicate and phosphate free, fully formulated nitrated organic acid technology
- Up to 300,000 mile life and up to 600,000 miles with extender

### Formulated to satisfy:

- ASTM D6210, D3306, SAE J1941, SAE J1034, TMC RP329, Truck Specifications: Caterpillar EC-1, Mack 14GS17004, Cummins CES 14603, Detroit Diesel 7SE 298 98 0

PRODUCT SIZES	
<b>PREDILUTED</b>	
FVPHDRED50/50-GAL	1 gal. 6/case
FVPHDRED50/50-55GA	55 gal drum



### Composition by Volume

Ethylene Glycol  
Soluble Inhibitors (Anhydrous)  
Total Water  
Dyes (Red)

### Properties

**Color**

**Odor**

**Ash Content** - ASTM D 1119

**pH** - 50% by Volume Solution - ASTM D 1287

**Reserve Alkalinity** - ASTM D 1121 - at 50% mixture

### Specific Gravity

at 20/20°C - 50% by Volume Solution - ASTM D 1122

### Freezing Point

40% by Volume Solution - ASTM D 1177

50% by Volume Solution - ASTM D 1177

60% by Volume Solution - ASTM D 1177

### Boiling Point†

40% by Volume Solution - ASTM D 1120

50% by Volume Solution - ASTM D 1120

60% by Volume Solution - ASTM D 1120

**Flash Point** (Tag Open Cup) 70% by Volume Solution

**Foam Test** - ASTM D 1881

**Average Net Weight/Gallon** at 68°F (20°C) 50 ml/2 sec.

† Atmospheric pressure

### Typical Values

46%  
2.2% min.  
2.8%  
Trace  
Red  
Characteristic  
2.5% max  
7.5 - 9.0  
1 mL  
1.120 - 1.13  
-10°F (-23°C)  
-34°F (-37°C)  
-62°F (-52°C)  
223°F (106°C)  
227°F (108°C)  
232°F (111°C)  
None  
None  
9-4 lbs.

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



**FACTORY MOTOR PARTS™**

WE SUPPLY YOUR SUCCESS.®