



GREASE



FVP High Temp Grease

FVP High Temp Grease is an exceptionally versatile multi-purpose grease, that provides a high-dropping point to protect over wide temperature ranges. Fully additive treated with EP/anti-wear, rust and oxidation inhibitors, and offers superior wheel bearing and chassis protection for a variety of severe-duty automotive, trucking, industrial, mining and construction equipment.



FVP General Purpose Grease

FVP General Purpose Grease is well suited for applications with normal temperature/speed conditions and service in contaminating environments. FVP General Purpose Grease works particularly well where extended lubrication intervals are practical, or where high-load or shock-loaded grease lubricated applications exist.



FVP Marine Grease

A high quality anhydrous calcium grease made with premium multi-purpose EP (Extreme Pressure) grease with extra water resistance. FVP Marine Grease is ideal for boat trailer wheel bearings. It is also compatible with lithium greases and is polymer fortified to improve performance when water is present. FVP Marine Grease's oxidation resistance provides enhanced protection and wear.

	High Temp HTRG-14	General Purpose MPG-14	Marine MG-14
NLGI Consistency Number	2	2	2
Thickener	Lithium Complex	Lithium Stearate	Anhydrous Calcium
Texture	Smooth Adhesive	Smooth	Smooth, Adhesive
Color	Red	Brown/Black	Green
Worked 60 Penetration, D-217	265-295	265-295	265-295
Dropping Point, D-2265, F.	500	320	290
Rust Prevention, D-1743, rating	Pass	Pass	Pass
Four-Ball EP Weld Point, D-2596, kgf	315	315	250
Timken OK Load, ASTM D2509, lb.	80	40	40
Approximate Temperature Range F.	-10 to 325	0 to 265	0 to 250

