



The Confident Solution.™

## 50/50 PREDILUTED ORIGINAL GREEN ANTIFREEZE/COOLANT



**FVP® 50/50 Prediluted Original Green Antifreeze/Coolant** protects all common cooling system metals including solder, copper, brass, steel, cast iron and aluminum. This low silicate formula provides excellent heat rejecting aluminum protection for all passenger and light duty truck cooling systems. FVP® 50/50 Prediluted Original Green Antifreeze/Coolant is a 50/50 blend of antifreeze/coolant concentrate with deionized and demineralized water that meets or exceeds the performance requirements of water in ASTM D 3306.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

**Product specifications when used as directed:**

- Meets ASTM D 3306
- Meets ASTM D 4985
- May be added to any conventional antifreeze/coolant
- Protects aluminum and any other engine metals

**[www.FVPparts.com](http://www.FVPparts.com)**  
**(866) FVP-EDGE • (866) 387-3343**

# 50/50 PREDILUTED ORIGINAL GREEN ANTIFREEZE/COOLANT

## Composition by Volume

Antifreeze/Coolant Concentrate  
Total Water  
Dyes (Green)

## Typical Values

51%  
49%  
Trace

## Properties

**Color**

Green

**Odor**

Characteristic

**Ash Content** - ASTM D 1119

1.5% max

**pH** - 50% by Volume Solution - ASTM D 1287

10.0 – 11.0

**Reserve Alkalinity** - ASTM D 1121

2.4

**Specific Gravity** at 20/20°C - 50% by Volume Solution - ASTM D 1122

1.064

**Freezing Point**

50% by Volume Solution - ASTM D 1177

-34°F (-37°C)

**Boiling Point†**

50% by Volume Solution - ASTM D 1120

227°F (108°C)

**Flash Point** (Tag Open Cup) 70% by Volume Solution

None

**Foam Test** - ASTM D 1881

50 ml/2 sec.

**Average Net Weight/Gallon** at 68°F (20°C)

8.9 lbs.

† Atmospheric pressure