



50/50 PREDILUTED ORIGINAL GREEN ANTIFREEZE/COOLANT



FVP® 50/50 Prediluted Original Green Antifreeze/Coolant protects all common cooling system metals including solder, copper, brass, steel, cast iron and aluminum. This low silicate formula provides excellent heat rejecting aluminum protection for all passenger and light duty truck cooling systems. FVP® 50/50 Prediluted Original Green Antifreeze/Coolant is a 50/50 blend of antifreeze/coolant concentrate with deionized and demineralized water that meets or exceeds the performance requirements of water in ASTM D 3306. Available in gallons.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

Product specifications when used as directed:

- Meets ASTM D 3306
- Meets ASTM D 4985
- May be added to any conventional antifreeze/coolant
- Protects aluminum and any other engine metals

50/50 PREDILUTED ORIGINAL GREEN ANTIFREEZE/COOLANT

Composition by Volume

Antifreeze/Coolant Concentrate
Total Water
Dyes (Green)

Typical Values

51%
49%
Trace

Properties

Color

Green

Odor

Characteristic

Ash Content - ASTM D 1119

1.5% max

pH - 50% by Volume Solution - ASTM D 1287

10.0 – 11.0

Reserve Alkalinity - ASTM D 1121

2.4

Specific Gravity at 20/20°C - 50% by Volume Solution - ASTM D 1122

1.064

Freezing Point

50% by Volume Solution - ASTM D 1177

-34°F (-37°C)

Boiling Point†

50% by Volume Solution - ASTM D 1120

227°F (108°C)

Flash Point (Tag Open Cup) 70% by Volume Solution

None

Foam Test - ASTM D 1881

50 ml/2 sec.

Average Net Weight/Gallon at 68°F (20°C)

8.9 lbs.

† Atmospheric pressure