

FVP LUBRICANTS

FULL SYNTHETIC dexos™1 Gen 3 MOTOR OIL



FVP Full Synthetic dexos™1 Gen 3 Motor Oils are formulated from select synthetic base stocks and advanced additive technology approved by General Motors to meet their current motor oil specification. The advanced additive package also provides unsurpassed protection against LSPI (Low Speed Pre-Ignition) for modern Gasoline Direct Injection (GDI) engines. The premium synthetic formulation delivers excellent oxidation stability and low volatility properties for maximizing oil drain intervals and resulting in reduced oil consumption between services. FVP Full Synthetic dexos™1 Gen 3 Motor Oils provide aggressive resistance to sludge formation and varnish deposits during stop-and-go driving.

FVP Full Synthetic dexos™1 Gen 3 Motor Oils are recommended for gasoline engines in passenger cars, SUVs, light vans and light trucks. The applications include GDI, multi-valve fuel injected, carbureted, turbocharged, and supercharged engines, and those needing to meet dexos™1 Gen 3 requirements.

- Optimized with low coefficient of friction for increased fuel efficiency and engine power output
- Formulated with anti-wear additives to provide maximum engine wear protection in harsh and demanding applications
- Superior oxidative stability provides resistance to high-temperature thermal breakdown and minimizes engine wear
- Excellent low-temperature performance protects crucial components during cold starts and operating environments
- Improved Low Speed Pre-Ignition (LSPI) protection to provide protection to engine components and maximize engine life
- Advanced shear stability and low volatility properties to support extended service intervals

PRODUCT SIZES	
0W20FSDEXOS-QT	6/ case
0W20FSDEXOS-55GAL	55 gal. drum
5W30FSDEXOS-QT	6/ case
5W30FSDEXOS-55GAL	55 gal. drum



SAE GRADE	0W-20	5W-30
Viscosity @ 40°C, cSt	45.9	55.1
Viscosity @ 100°C, cSt	8.6	9.9
Viscosity Index	168	168
Cold Crank Simulation, cP	4,912 @ -35°C	3,744 @ -30°C
HTHS @ 150°C, cP	2.6	2.9
Pour Point: °C (°F)	-42 (-44)	-45 (-49)
Flash Point: °C (°F)	232 (450)	226 (440)
Density @ 15°C, g/mL	.848	.846
API: RC (Resource Conserving)	YES	YES
ILSAC GF-7A Certified	YES	YES
dexos™1 Gen 3	X	X
API Licensed Service	SQ and prior	SQ and prior
Chrysler MS-6395	X	X
Ford WSS-M2C972-A1	X	
Ford WSS-M2C971-A1		X

X = Recommended for use / meets requirements

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™
WE SUPPLY YOUR SUCCESS.®