

50/50 PREDILUTED FORMULA ORIGINAL GREEN ANTIFREEZE/ COOLANT



50/50 PREDILUTED FORMULA

FVP® 50/50 Prediluted Original Green Antifreeze/Coolant protects all common cooling system metals including solder, copper, brass, steel, cast iron and aluminum. This low silicate formula provides excellent heat rejecting aluminum protection for all passenger and light duty truck cooling systems. FVP® 50/50 Prediluted Original Green Antifreeze/Coolant is a 50/50 blend of antifreeze/coolant concentrate with deionized and demineralized water that meets or exceeds the performance requirements of water in ASTM D 3306. Available in gallons.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

Product specifications when used as directed:

- Meets ASTM D 3306
- Meets ASTM D 4985
- May be added to any conventional antifreeze/coolant
- Helps prevent freeze-ups, overheating, and boil overs
- Protects aluminum and any other engine metals

PRODUCT SIZES

FVPGREEN50/50-GAL	1 gal.	6/case
-------------------	--------	--------



Composition by Volume

Antifreeze/Coolant 51%
Total Water 49%
Dyes (Green) Trace

Properties

Color

Odor

Ash Content - ASTM D 1119

pH - 50% by Volume Solution - ASTM D 1287

Reserve Alkalinity - ASTM D 1121

Specific Gravity

at 20/20°C - 50% by Volume Solution - ASTM D 1122

Freezing Point

50% by Volume Solution - ASTM D 1177

Boiling Point†

50% by Volume Solution - ASTM D 1120

Flash Point (Tag Open Cup) 70% by Volume Solution

Foam Test - ASTM D 1881

Average Net Weight/Gallon at 68°F (20°C)

† Atmospheric pressure

Typical Values

51%
49%
Trace

Green

Characteristic

.23% max

10.8

2.8

1.0712

-34°F [-37°C]

227°F [108°C]

None

50 ml/1 sec.

8.9 lbs.

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts. ©Copyright 2019 Factory Motor Parts.



FACTORYMOTORPARTS™

WE SUPPLY YOUR SUCCESS.®