

FVP 5 QUART LUBRICANTS

FULL SYNTHETIC MOTOR OIL



MAXIMUM ENGINE PROTECTION & PERFORMANCE

FVP Full Synthetic Motor Oils is formulated with higher quality synthetic base oils and premium additive technology to provide exceptional engine protection even under the extremes of potential operating temperature. It is designed for applications requiring the use of a synthetic grade or for severe service under heavy load operation or extended drain, where the performance benefits of a synthetic oil ensure optimum lubrication.

FVP Full Synthetic Motor Oils engine oil is formulated to provide robust performance against all of the key performance elements of the GF-6 specification ensuring that it not only fully meets the warranty requirements of newer turbocharged gasoline direct injection (TGDI) engine types in terms of wear, oxidation control, fuel economy and pre-ignition, but also continues to provide excellent protection against sludge, piston cleanliness, engine rust and corrosion for all engine types under severe service or low temperature operation.

Industry and OEM Applications

- API SP, SN Plus and prior "S" categories
- ILSAC GF-6A and GF-6B 1, Resource Conserving
- Chrysler MS-6395S
- Meets the requirements for FORD:
 - WSS-M2C960-A1 (5W-20) 2
 - WSS-M2C961-A1 (5W-30) 2
- Toyota, Honda, Nissan, and Hyundai ³



SAE GRADE	5W-20	10W-30
Viscosity @ 40°C, cSt	47.93	69.29
Viscosity @ 100°C, cSt	8.493	10.87
Viscosity Index	155	147
Specific Gravity @ 60°F	0.8536	0.8542
Pour Point, °C	-39	-39
Color ASTM	L3.0	L3.0
Cold Crank Simulator, cP	4,912 (-30°C)	4,982 (-25°C)
Flash Point, °C	226	251
TBN, mg KOH/g	7.3	7.2
Noack Volatility, %	8.6	5.7
HTHS, cP	2.60	3.00

PRODUCT SIZES

5W20FS-5QT	4/ case
10W30FS-5QT	4/ case

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™

WE SUPPLY YOUR SUCCESS.®