

FULL SYNTHETIC

ATF+4 AUTOMATIC TRANSMISSION FLUID



SUPERIOR ADDITIVE TECHNOLOGY

FVP Full Synthetic ATF+4 is a balanced advanced formula utilizing superior additive technology and 100% synthetic base oils helping to ensure peak performance of almost any automatic transmission while offering:

- Excellent protection against wear and shudder resistance
- Resistance to thickening due to high temperatures
- Stable friction properties for smooth and consistent shifting
- Excellent shear stability
- Available in quarts (ATF4-QT).

Applications

FVP ATF+4 Transmission Fluid is designed to meet the specific requirements of Chrysler and FCA automatic transmissions/transaxles and certain Hyundai and Mitsubishi transmissions.

FVP Full Synthetic ATF+4 is formulated as for use in Chrysler ATF+4 (MS 9602) and suitable for use in Chrysler ATF+3 (MS 7176E).

SAE GRADE

Brookfield viscosity at -40°C, cP	ASTM D2983	9,000
Color	ASTM D1500	Red
Gravity, °API	ASTM D287	34.81
Pour Point: °C	ASTM D5950	-48° (-54°F)

Specific Gravity @60°F (15.6°)

Viscosity @ 40°C, cSt	ASTM D445	35.22
Viscosity @ 100°C, cSt	ASTM D445	7.68
Viscosity Index	ASTM D2270	201



REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™

WE SUPPLY YOUR SUCCESS.®