



# FULL STRENGTH ORANGE FORMULA ANTIFREEZE/COOLANT



**FVP® Full Strength Orange Formula Antifreeze/Coolant** can be used in place of Dex-Cool® coolant in all General Motors® cars and light duty trucks. FVP® Full Strength Orange Formula Antifreeze/Coolant is compatible and formulated for use with ANY antifreeze/coolant in ANY make or model of car or light duty truck and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to offer protection for up to 5 years or 150,000 miles\* against temperature extremes, the ravages of rust and corrosion, and premature water pump failure when used as directed. Available in gallons.

\* Always consult the owner's manual to determine the specific maintenance and change intervals for the vehicle

\* DEX-COOL is a registered trademark of GM Corporation

**Product Specifications when used as directed:**

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/ coolant of ANY make and model of automobile and light duty truck on the road, foreign or domestic
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications

# FULL STRENGTH ORANGE FORMULA ANTIFREEZE/COOLANT

## Composition by Volume

Ethylene Glycol	Typical Values
Soluble Inhibitors (Anhydrous)	92.8%
Total Water	4.9%
Dyes (Orange)	2.3%
	Trace

## Properties

<b>Color</b>	Orange
<b>Odor</b>	Characteristic
<b>Ash Content - ASTM D 1119</b>	1.26% by weight
<b>pH - 50% by Volume Solution - ASTM D 1287</b>	8.7
<b>Reserve Alkalinity - ASTM D 1121</b>	11.2
<b>Specific Gravity at 20/20°C - 50% by Volume Solution - ASTM D 1122</b>	1.0687
<b>Freezing Point</b>	
50% by Volume Solution - ASTM D 1177	-34°F (-37°C)
<b>Boiling Point†</b>	
50% by Volume Solution - ASTM D 1120	226°F (108°C)
<b>Flash Point (Tag Open Cup) 70% by Volume Solution</b>	None
<b>Foam Test - ASTM D 1881</b>	50 ml/2 sec
<b>Average Net Weight/Gallon at 68°F (20°C)</b>	9.3 lbs.

† Atmospheric pressure