

## FULL SYNTHETIC MOTOR OIL



**FVP Full Synthetic Motor Oils** are premium quality motor oils formulated from selected superior base oils with advanced additive technology to provide the highest level of protection available. FVP Full Synthetic Motor Oils meet or exceed the latest American Petroleum Institute (API) SN-RC and car manufacturers ILSAC GF-5 service classification. FVP Full Synthetic Motor Oils are designed especially for turbo-charged and high RPM engines which experience high heat. They provide quick flow to critical parts at start up to reduce wear. FVP Full Synthetic Motor Oils are the engine oils of choice for passenger cars, light trucks, power boats, motorcycles and other stationary and mobile equipment when engine life and performance is important.

## Available in quarts and 55 gallon drums

- 0W-20
- 5W-20
- 5W-30
- 10W-30

www.FVPparts.com (866) FVP-EDGE • (866) 387-3343

## FULL SYNTHETIC MOTOR OIL

SAE GRADE	0W-20	5W-20	5W-30	10W-30
Density, lb/gal	7.1	7.2	7.12	7.11
API Gravity	35.52	34.95	34.85	34.05
Cold Crank Simulation, mPa/s	6100	3900	6600 Max	7000 Max
Viscosity @ 100°C, cSt	6.6-9.0	8.0-8.8	9.7-11.5	9.7-11.7
Viscosity Index	150-190	140-160	145-168	125-150
NOACK	15 Max	15 Max	12	15 Max
Color ASTM	3 Max	3 Max	3 Max	3 Max
Water And Sediment (Pass/Fail)	Pass	Pass	Pass	Pass
Appearance	Clear	Clear	Clear	Clear
Pour Point: °C	-48	-45	-45	-42
Flash Point: °C	216	225	240	250
Са	1760-2050	1760-2050	1760-2050	1760-2050
P	706-842	706-842	706-842	706-842
Zn	782-918	782-918	782-918	782-918
API: RC (Resource Conserving)	YES	YES	YES	NO
ILSAC GF-5 Certified:	YES	YES	YES	NO
API Licensed Service:	SN, SM, SL, SJ			