



# 50/50 PREDILUTED ORANGE FORMULA ANTIFREEZE/COOLANT



**FVP® 50/50 Prediluted Orange Formula Antifreeze/Coolant** may be used in all General Motors vehicles that require DEX-COOL® Coolant. This formula has a diluted blend of premium long-lasting inhibitors to offer protection for up to 5 years or 150,000 miles against temperature extremes and the ravages of rust, corrosion, and premature water pump failure. This extended life protection is best provided when the cooling system is flushed and filled. Available in gallons.

\* Always consult the owner's manual to determine the specific maintenance and change intervals for the vehicle

\* DEX-COOL is a registered trademark of GM Corporation

**Product Specifications when used as directed:**

- Meets ASTM D 3306, ASTM D 4985
- May be added to conventional antifreeze/coolant
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications

# 50/50 PREDILUTED ORANGE FORMULA ANTIFREEZE/COOLANT

## Composition by Volume

Antifreeze/Coolant Concentrate  
Total Water  
Dyes (Orange)

## Typical Values

51%  
49%  
Trace

## Properties

**Color**

Orange

**Odor**

Characteristic

**Ash Content** - ASTM D 1119

1.5% max

**pH** - 50% by Volume Solution - ASTM D 1287

10.0 – 11.0

**Reserve Alkalinity** - ASTM D 1121

2.4

**Specific Gravity** at 20/20°C - 50% by Volume Solution - ASTM D 1122

1.064

**Freezing Point**

50% by Volume Solution - ASTM D 1177

-34°F (-37°C)

**Boiling Point†**

50% by Volume Solution - ASTM D 1120

227°F (108°C)

**Flash Point** (Tag Open Cup) 70% by Volume Solution

None

**Foam Test** - ASTM D 1881

50 ml/2 sec.

**Average Net Weight/Gallon** at 68°F (20°C)

8.9 lbs.

† Atmospheric pressure