

FVP LUBRICANTS

SYNTHETIC BLEND MOTOR OIL



ADVANCED PROTECTION AGAINST THERMAL BREAKDOWN

FVP Synthetic Blend Motor Oils are formulated from premium synthetic-blend base stocks and advanced additive technology to deliver trusted engine protection and peak vehicle performance. FVP Synthetic Blend Motor Oils provide added resistance to sludge formation and varnish deposits during stop-and-go driving and maintain outstanding wear protection under severe conditions. The additive package also provides protection against Low Speed Pre-Ignition (LSPI) for modern Gasoline Direct Injection (GDI) engines.

FVP Synthetic Blend Motor Oils are recommended for gasoline engines in passenger cars, SUVs, light vans and light trucks. The applications include GDI, multi-valve fuel injected, carbureted, turbocharged, and supercharged engines.

- Optimized for increased fuel efficiency and engine power output
- Maximum engine wear protection in harsh and demanding applications
- Advanced detergents minimize deposits and maximize engine power and efficiency
- Robust oxidative stability provides maximum resistance to high-temperature thermal breakdown to minimize engine wear
- Improved Low Speed Pre-Ignition (LSPI) protection to engine components and maximize engine life

PRODUCT SIZES

5W20SB-QT	12/ case
5W20SB-55GAL	55 gal. drum
5W30SB-QT	12/ case
5W30SB-55GAL	55 gal drum
10W30SB-QT	12/ case
10W30SB-55GAL	55 gal. drum
10W40SB- QT	12/ case
10W40SB-55GAL	55 gal. drum
20W50SB- QT	12/ case
20W50SB-55GAL	55 gal. drum



SAE GRADE	5W-20	5W-30	10W-30	10W-40	20W50
Viscosity @ 40°C, cSt	49.1	61.8	63.5	93.4	124.5
Viscosity @ 100°C, cSt	8.6	10.3	10.3	14.7	17.8
Viscosity Index	152	155	150	164	159
Cold Crank Simulation, cP	5,377 @ -30°C	4,218 @ -30°C	4,170 @ -25°C	4,060 @ -25°C	7,855 @ 15°C
HTHS @ 150°C, cP	2.7	3.0	3.0	3.7	4.6
Pour Point: °C (°F)	-45 (-49)	-42 (-44)	-42 (-44)	-44 (-47)	-36 (-33)
Flash Point: °C (°F)	226 (440)	232 (450)	226 (440)	232 (450)	232 (450)
Density @ 15°C, g/mL	.856	.859	.858	.858	.878
API: RC (Resource Conserving)	YES	YES	YES	NO	NO
ILSAC GF-7A Certified	YES	YES	YES	NO	NO
API Licensed Service	SQ and prior	SQ and prior	SQ and prior	SQ and prior	SQ and prior
Chrysler MS-6395	X	X	X		
Ford WSS-M2C970-A1	X				
Ford WSS-M2C971-A1		X			
GM 6094M			X		

X = Recommended for use / meets requirements

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™
WE SUPPLY YOUR SUCCESS.®