Safety Data Sheet

Issue Date: 17-Nov-2020 Revision Date: 17-Nov-2020 Version 1

1. IDENTIFICATION

Product identifier

Product Name Stay Tuned Multi-System Additive

Other means of identification

SDS#/Part# 176578-72

Recommended use of the chemical and restrictions on use

Recommended Use For industrial use.

Details of the supplier of the safety data sheet

Manufacturer Address

FMP

1380 Corporate Center Curve, Suite 200

Eagan, MN 55121 Phone: 888-784-0802

Emergency telephone number

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Yellow to brown liquid Physical state Liquid Odor Typical

Classification

Carcinogenicity	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 4

Signal Word Danger

Hazard statements

Suspected of causing cancer May be fatal if swallowed and enters airways Combustible liquid



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Petroleum Distillates, Hydrotreated light	64742-47-8	85-90
Xylene	1330-20-7	1-5
Light aliphatic solvent naphtha	64742-48-9	0.1-1
Ethylbenzene	100-41-4	0.1-1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

General Advice If exposed or concerned: Get medical advice/attention.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes.

Inhalation Remove to fresh air.

Immediately call a poison center or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms May be harmful in contact with skin. Causes mild skin irritation. Suspected of causing

cancer. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use CO2, dry chemical, or foam for extinction.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Combustible liquid.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal PrecautionsUse personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Use personal protective equipment as required. Keep away from

heat/sparks/open flames/hot surfaces. — No smoking.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Store in a well-ventilated place. Keep cool.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Yellow to brown liquid Odor Typical

Color Yellow to brown Odor Threshold Not determined

Property Values Remarks • Method

pH Not determined
Melting point / freezing point
Boiling point / boiling range 147.8 °C / 298 °F
Flash point 61.1 °C / 142 °F
Evaporation Rate Not determined
Flammability (Solid, Gas) Liquid-Not applicable

Flammability Limit in Air

Upper flammability or explosive 6.0

limits

Lower flammability or explosive 0.8

limits

Vapor PressureNot determinedVapor DensityNot determined

Relative Density 0.814

Water Solubility Not determined Solubility in other solvents Not determined **Partition Coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined Kinematic viscosity Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact May be harmful in contact with skin.

Inhalation Do not inhale.

Ingestion Do not ingest.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Distillates, Hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Light aliphatic solvent naphtha 64742-48-9	> 6000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 8500 mg/m³(Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes mild skin irritation.

Carcinogenicity Suspected of causing cancer.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

 Oral LD50
 5,589.70 mg/kg

 Dermal LD50
 2,225.50 mg/kg

 Gas
 52,238.80 mg/L

 ATEmix (inhalation-dust/mist)
 140.20 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum Distillates, Hydrotreated		45: 96 h Pimephales promelas mg/L	4720: 96 h Den-dronereides
light		LC50 flow-through 2.2: 96 h	heteropoda mg/L LC50
64742-47-8		Lepomis macrochirus mg/L LC50	
		static 2.4: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	
Paraffins (petroleum), normal C5-20		5000: 96 h Pimephales promelas	
64771-72-8		mg/L LC50 static	
Xylene		13.1 - 16.5: 96 h Lepomis	0.6: 48 h Gammarus lacustris mg/L
1330-20-7		macrochirus mg/L LC50 flow-	LC50 3.82: 48 h water flea mg/L
		through 19: 96 h Lepomis	EC50
		macrochirus mg/L LC50 23.53 -	
		29.97: 96 h Pimephales promelas	
		mg/L LC50 static 7.711 - 9.591: 96 h	
		Lepomis macrochirus mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 2.661 -	
		4.093: 96 h Oncorhynchus mykiss	
		mg/L LC50 static 30.26 - 40.75: 96 h	
		Poecilia reticulata mg/L LC50 static	
		13.5 - 17.3: 96 h Oncorhynchus	
		mykiss mg/L LC50 13.4: 96 h	
		Pimephales promelas mg/L LC50	
		flow-through 780: 96 h Cyprinus	
		carpio mg/L LC50	
Light aliphatic solvent naphtha		2200: 96 h Pimephales promelas	2.6: 96 h Chaetogammarus marinus
64742-48-9		mg/L LC50	mg/L LC50
Ethylbenzene	2.6 - 11.3: 72 h Pseudokirchneriella	4.2: 96 h Oncorhynchus mykiss	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 static 1.7 -	mg/L LC50 semi-static 7.55 - 11: 96	EC50
	7.6: 96 h Pseudokirchneriella	h Pimephales promelas mg/L LC50	
	subcapitata mg/L EC50 static 438:	flow-through 11.0 - 18.0: 96 h	
	96 h Pseudokirchneriella	Oncorhynchus mykiss mg/L LC50	
	subcapitata mg/L EC50 4.6: 72 h	static 32: 96 h Lepomis macrochirus	
	Pseudokirchneriella subcapitata	mg/L LC50 static 9.1 - 15.6: 96 h	
	mg/L EC50	Pimephales promelas mg/L LC50	
		static 9.6: 96 h Poecilia reticulata	
		mg/L LC50 static	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Xylene 1330-20-7	3.15
Chemical name	Partition coefficient

Ethylbenzene	3.2
100-41-4	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene		Included in waste stream:		U239
1330-20-7		F039		
Ethylbenzene		Included in waste stream:		
100-41-4		F039		

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status	
Xylene	Toxic	
1330-20-7	Ignitable	
Ethylbenzene Toxic		
100-41-4	Ignitable	

14. TRANSPORT INFORMATION

Note According to 49 CFR §173.150(f)(1), this material should be reclassified as "NA1993,

Combustible Liquid, N.O.S." if it is shipped in bulk.

DOT Not regulated

IATA Not regulated

<u>IMDG</u> Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory	DSL/NDSL	EINECS/ELI	ENCS	IECSC	KECL	PICCS	AICS
		Status		NCS					
Petroleum Distillates, Hydrotreated light	Х	ACTIVE	X	Х		Х	Х	X	Х
Paraffins (petroleum), normal C5-20	Х	ACTIVE	Х	Х		Х	Х	Х	Х
Xylene	Χ	ACTIVE	X	X	Χ	X	Х	X	X
Light aliphatic solvent naphtha	Х	ACTIVE	X	X		X	X	X	X
Ethylbenzene	Х	ACTIVE	Х	X	Х	Х	X	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

SARA 313

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	1-5	1.0
Ethylbenzene - 100-41-4	100-41-4	0.1-1	0.1

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene	100 lb			X
Ethylbenzene	1000 lb	X	X	X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65	
Ethylbenzene - 100-41-4	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Ethylbenzene 100-41-4	X	X	Х

16. OTHER INFORMATION

NFPA Health Hazards

Not determined
Health Hazards
Not determined

Flammability
Not determined
Flammability
Not determined

Instability
Not determined
Physical hazards
Not determined

Special Hazards
Not determined
Personal Protection
Not determined

Issue Date:17-Nov-2020Revision Date:17-Nov-2020Revision Note:New format

Disclaimer

HMIS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet