ORANGE ANTIFREEZE/ COOLANT

50/50 PREDILUTED FORMULA

FVP® 50/50 Prediluted Orange Formula Antifreeze/Coolant may be used in all General Motors vehicles that require DEX-COOL® Coolant. This formula has a diluted blend of premium long-lasting inhibitors to offer protection for up to 5 years or 150,000 miles against temperature extremes and the ravages of rust, corrosion, and premature water pump failure. This extended life protection is best provided when the cooling system is flushed and filled. Available in gallons and 55 gallon drums.

- *-DEX-COOL is a registered trademark of GM Corporation
- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

Product specifications when used as directed:

- Meets ASTM D 3306. D4985
- May be added to the antifreeze/ coolant of ANY make and model of automobile and light duty truck on the road, foreign or domestic
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications
- Free of phosphates, borates, nitrites, silicates and amines
- Compatible with orange OAT fluids

PRODUCT SIZES		
FVPDEX-50/50GAL	1 gal.	6/case
FVPDEX50/50-DRUM	55 gal	drum





Composition by Volume Antifreeze/Coolant Total Water Dyes (Orange) Properties Color Odor Ash Content - ASTM D 1119 pH - 50% by Volume Solution - ASTM D 1287 Reserve Alkalinity - ASTM D 1121 Specific Gravity at 20/20°C - 50% by Volume Solution - ASTM D 1122 Freezing Point 50% by Volume Solution - ASTM D 1177 Boiling Point, under standard pressure 50% by Volume Solution - ASTM D 1120 Flash Point (Tag Open Cup) 70% by Volume Solution Foam Test - ASTM D 1881 Average Net Weight/Gallon at 68°F (20°C)

Trace
Orange
Characteristic
.54% max
8.7
2.6

Typical Values

51%

49%

-34°F (-37°C)

?27°F (108°C) None 50 ml/1 sec 8.9 lbs.



FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS

WE SUPPLY YOUR SUCCESS.