

FVP LUBRICANTS

FULL SYNTHETIC MOTOR OIL



MAXIMUM ENGINE PROTECTION & PERFORMANCE

FVP Full Synthetic Motor Oils are formulated from select full-synthetic base stocks and advanced additive technology to deliver trusted engine protection and peak vehicle performance. FVP Full Synthetic Motor Oils provide aggressive resistance to sludge formation and varnish deposits during stop-and-go driving. The advanced additive package also provides unsurpassed protection against LSPI (Low Speed Pre-Ignition) for modern Gasoline Direct Injection (GDI) engines. The premium synthetic formulation delivers excellent oxidation stability and low volatility properties for maximizing oil drain intervals and resulting in reduced oil consumption between services.

FVP Full Synthetic Motor Oils are recommended for gasoline engines in passenger cars, SUVs, light vans and light trucks. The applications include GDI, multi-valve fuel injected, carbureted, turbocharged, and supercharged engines.

- Optimized for increased fuel efficiency and engine power output
- Maximum engine wear protection in harsh and demanding applications
- Superior oxidative stability provides resistance to high-temperature thermal breakdown and minimizes engine wear
- Excellent low-temperature performance protects crucial components during cold starts and operating environments
- Improved Low Speed Pre-Ignition (LPSI) protection to maximize engine life
- Advanced shear stability and low volatility properties to support extended service intervals

PRODUCT SIZES

0W20FS-QT	6/ case
0W20FS-55GAL	55 gal. drum
5W20FS-QT	6/ case
5W20FS-55GAL	55 gal. drum
5W30FS-QT	6/ case
5W30FS-55GAL	55 gal drum
10W30FS-QT	6/ case
10W30FS-55GAL	55 gal. drum



SAE GRADE	0W-20	5W-20	5W-30	10W-30
Viscosity @ 40°C, cSt	45.7	48.9	57.5	69.0
Viscosity @ 100°C, cSt	8.7	8.8	10.2	11.1
Viscosity Index	173	161	168	153
Cold Crank Simulation, cP	5,418 @ -35°C	4,567 @ -30°C	4,400 @ 30°C	4,463 @ 25°C
HTHS @ 150°C, cP	2.6	2.8	3.0	3.2
Pour Point: °C (°F)	-42 (-44)	-39 (-38)	-39 (-38)	-39 (-38)
Flash Point: °C (°F)	232 (450)	226 (440)	232 (450)	232 (450)
Density @ 15°C, g/mL	.844	.848	.847	.853
API: RC (Resource Conserving)	YES	YES	YES	YES
ILSAC GF-7A Certified	YES	YES	YES	YES
API Licensed Service	SQ and prior	SQ and prior	SQ and prior	SQ and prior
Chrysler MS-6395	X	X	X	X
Ford WSS-M2C972-A1	X		X	
Ford WSS-M2C970-A1		X		
Ford WSS-M2C971-A1			X	
GM 6094M				X

X = Recommended for use / meets requirements

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™
WE SUPPLY YOUR SUCCESS.®