

50/50 PREDILUTED FORMULA MULTI-VEHICLE ANTIFREEZE/ COOLANT

50/50 PREDILUTED FORMULA

FVP® 50/50 Prediluted Multi-Vehicle Antifreeze/Coolant is recommended, compatible, and formulated for use with any antifreeze/coolant in any vehicle with aluminum and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to guard against temperature extremes and ravages of rust, corrosion, and premature water pump failure. FVP® 50/50 Prediluted Multi-Vehicle Antifreeze/Coolant is a 50/50 blend of antifreeze/coolant concentrate and demineralized water that provides extended life protection for cars and light-duty trucks up to 5 years or 150,000 miles* when added to any extended life coolant. Available in gallons and 55 gallon drums.

*- Compatible with other extended life and conventional coolants.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.



Product specifications when used as directed:

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/coolant of any make and model of automobile and light duty truck on the road, foreign or domestic
- May be added to any color antifreeze/coolant (color may change, but performance will not be affected)
- Protects aluminum and any other engine metals
- Free of phosphates, borates, nitrites, silicates and amines
- Universally works with all fluid colors; all OAT, POAT, HOAT & IAT

PRODUCT SIZES

| | | |
|-----------------|--------|--------|
| FVPMV50/50-GAL | 1 gal. | 6/case |
| FVPMV50/50-DRUM | 55 gal | drum |



Composition by Volume

Antifreeze/Coolant

Total Water

Dyes (Yellow)

Properties

Color

Odor

Ash Content - ASTM D 1119

pH - 50% by Volume Solution - ASTM D 1287

Reserve Alkalinity - ASTM D 1121

Specific Gravity

at 20/20°C - 50% by Volume Solution - ASTM D 1122

Freezing Point

50% by Volume Solution - ASTM D 1177

Boiling Point, under standard pressure

50% by Volume Solution - ASTM D 1120

Flash Point (Tag Open Cup) 70% by Volume Solution

Foam Test - ASTM D 1881

Average Net Weight/Gallon at 68°F (20°C)

Typical Values

51%

49%

Trace

Yellow

Characteristic

.4% max

8.7

1.0

1.0694

-34°F (-37°C)

227°F (108°C)

None

50 ml/2.2 sec

8.9 lbs.

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™

WE SUPPLY YOUR SUCCESS.®