



SYNTHETIC BLEND MOTOR OIL



FVP Synthetic Blend Motor Oils are premium quality synthetic blend engine oils formulated from selected superior base oils with advanced high performance additive technology. FVP Synthetic Blend Motor Oils are formulated with low friction additives to help improve fuel economy where synthetic oils are recommended to provide outstanding engine protection. FVP Synthetic Blend Motor Oils are licensed to meet or exceed the latest automotive manufacturers requirements of API SN and SN-RC. 5W-20, 5W-30 and 10W-30 are fully licensed to meet and exceed ILSAC GF-5 requirements for use in passenger car engines. FVP Synthetic Blend Motor Oils show improved high temperature deposit control, oil consumption and fuel economy. FVP Synthetic Blends provide better low temperature pumpability.

Available in quarts and 55 gallon drums:

- 5W-20
- 5W-30
- 10W-30
- 10W-40
- 20W-50

SYNTHETIC BLEND MOTOR OIL

SAE GRADE	5W-20	5W-30	10W-30	10W-40	20W-50
Viscosity @ 100°C, cSt	8.0-8.8	9.7-11.5	9.7-11.7	13.0-15.5	16.6-21.5
Viscosity Index	140-160	145-168	125-150	130-155	120-150
API Gravity	32.78	33.01	31.51	31.74	29.77
Pour Point: °C	-48	-48	-42	-42	-36
Color	3 Max	3 Max	3 Max	3 Max	3.5 Max
API: RC (Resource Conserving)	YES	YES	YES	NO	NO
ILSAC GF-5 Certified:	YES	YES	YES	NO	NO
API Licensed Service:	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ