



The Confident Solution.™

FULL STRENGTH MULTI-VEHICLE ANTIFREEZE/COOLANT



FVP® Full Strength Multi-Vehicle Antifreeze/Coolant is recommended, compatible, and formulated for use with any antifreeze/coolant in any vehicle with aluminum and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to guard against temperature extremes and ravages of rust, corrosion, and premature water pump failure. FVP® Full Strength Multi-Vehicle Antifreeze/Coolant provides extended life protection for cars and light-duty trucks up to 5 years or 150,000 miles* when added to any extended life coolant or when flushed and filled according to directions.

*- Compatible with other extended life and conventional coolants.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

Product specifications when used as directed:

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/coolant of any make and model of automobile and light duty truck on the road, foreign or domestic
- May be added to any color antifreeze/coolant (color may change, but performance will not be affected)
- Protects aluminum and any other engine metals

www.FVPparts.com

(866) FVP-EDGE • (866) 387-3343

FULL STRENGTH MULTI-VEHICLE ANTIFREEZE/COOLANT

Composition by Volume

Ethylene Glycol	93.8%
Soluble Inhibitors (Anhydrous)	4.2%
Total Water	2.0%
Dyes (Yellow)	Trace

Properties

Color	Yellow
Odor	Characteristic
Ash Content - ASTM D 1119	1.2% by weight
pH - 50% by Volume Solution - ASTM D 1287	
Reserve Alkalinity - ASTM D 1121	2.0
Specific Gravity at 20/20°C - 50% by Volume Solution - ASTM D 1122	1.0687
Freezing Point - 50% by Volume Solution - ASTM D 1177	-34°F (-37°C)
Boiling Point† - 50% by Volume Solution - ASTM D 1120	226°F (108°C)
Flash Point (Tag Open Cup) 70% by Volume Solution	None
Foam Test - ASTM D 1881	50 ml/1 sec.
Average Net Weight/Gallon at 68°F (20°C)	9.3 lbs.

† Atmospheric pressure