

SYNTHETIC BLEND Motor Oil



FVP Synthetic Blend Motor Oils are premium quality synthetic blend engine oils formulated from selected superior base oils with advanced high performance additive technology. FVP Synthetic Blend Motor Oils are formulated with low friction additives to help improve fuel economy where synthetic oils are recommended to provide outstanding engine protection. FVP Synthetic Blend Motor Oils are licensed to meet or exceed the latest automotive manufacturers requirements of API SN and SN-RC. 5W-20, 5W-30 and 10W-30 are fully licensed to meet and exceed ILSAC GF-5 requirements for use in passenger car engines. FVP Synthetic Blend Motor Oils show improved high temperature deposit control, oil consumption and fuel economy. FVP Synthetic Blends provide better low temperature pumpability.

Available in quarts and 55 gallon drums:

- 5W-20
- 5W-30
- 10W-30
- 10W-40
- 20W-50

www.FVPparts.com (866) FVP-EDGE • (866) 387-3343

SYNTHETIC BLEND Motor Oil

| SAE GRADE | 5W-20 | 5W-30 | 10W-30 | 10W-40 | 20W-50 |
|----------------------------------|----------------|----------------|----------------|----------------|----------------|
| Viscosity @ 100°C, cSt | 8.0-8.8 | 9.7-11.5 | 9.7-11.7 | 13.0-15.5 | 16.6-21.5 |
| Viscosity Index | 140-160 | 145-168 | 125-150 | 130-155 | 120-150 |
| API Gravity | 32.78 | 33.01 | 31.51 | 31.74 | 29.77 |
| Pour Point: °C | -48 | -48 | -42 | -42 | -36 |
| Color | 3 Max | 3 Max | 3 Max | 3 Max | 3.5 Max |
| API: RC (Resource Conserving) | YES | YES | YES | NO | NO |
| ILSAC GF-5 Certified: | YES | YES | YES | NO | NO |
| API Licensed Service: | SN, SM, SL, SJ |