

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product name : FVP FUEL INJECTOR CLEANER
Product code : 2112

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel System cleaner.

1.3. Details of the supplier of the safety data sheet

Factory Motor parts
1380 Corporate Center Curve, #200
Eagan, MN 55121
866-387-3343
Emergency number : Infotrac 1-800-535-5053

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid 2
Skin irritation 2
Carcinogenicity 2
Specific target organ toxicity - Single exposure 3
Aspiration hazard 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) : Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

4 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Kerosine, petroleum	(CAS No) 8008-20-6	60 - 100	Flam. Liq. 3 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Polyolefin alkyl phenol alkyl amine	Proprietary	1 - 2	Skin Irrit. 2 Eye Irrit. 2A
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	0.5 - 1.5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Naphthalene	(CAS No) 91-20-3	< 0.5	Acute Tox. 4 (Oral) Carc. 2
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Acute Tox. 4 (Oral) Carc. 2 STOT SE 3 Asp. Tox. 1
Ethylbenzene	(CAS No) 100-41-4	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2
Toluene	(CAS No) 108-88-3	< 0.1	Flam. Liq. 2 Skin Irrit. 2 Repr. 2 (developmental) STOT SE 3 STOT RE 2 Asp. Tox. 1
Benzene	(CAS No) 71-43-2	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1A STOT RE 1 Asp. Tox. 1
Furan	(CAS No) 110-00-9	< 0.1	Flam. Liq. 1 Acute Tox. 4 (Oral) Acute Tox. 3 (Inhalation) Skin Irrit. 2 Muta. 2 Carc. 1B STOT RE 2
Propylene oxide	(CAS No) 75-56-9	< 0.1	Flam. Liq. 1 Acute Tox. 3 (Inhalation) Acute Tox. 4 (Oral, Dermal) Eye Irrit. 2A Muta. 1B Carc. 2 STOT SE 3
Acetaldehyde	(CAS No) 75-07-0	< 0.1	Flam. Liq. 1 Eye Irrit. 2A Carc. 2 STOT SE 3

* The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Kerosine, petroleum (8008-20-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	200 mg/m ³
Polyolefin alkyl phenol alkyl amine (Proprietary)		
ACGIH	Not applicable	
OSHA	Not applicable	

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Benzene, 1,2,4-trimethyl- (95-63-6)		
ACGIH	Not applicable	
OSHA	Not applicable	

Naphthalene (91-20-3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

Cumene (98-82-8)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

Ethylbenzene (100-41-4)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm
USA ACGIH	ACGIH STEL (ppm)	2.5 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	5 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm

Furan (110-00-9)		
ACGIH	Not applicable	
OSHA	Not applicable	

Propylene oxide (75-56-9)		
USA ACGIH	ACGIH TWA (ppm)	2 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Acetaldehyde (75-07-0)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	360 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

8.2. Exposure controls

- | | |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Appropriate engineering controls | : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. |
| Personal protective equipment | : Avoid all unnecessary exposure. |
| Hand protection | : Wear chemically resistant protective gloves. |
| Eye protection | : Safety glasses or goggles are recommended when using product. |
| Skin and body protection | : Wear suitable protective clothing. |

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear
Color	: Amber
Odor	: Petroleum odor
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 22 °C (71 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.864 - 0.869
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified.
----------------	-------------------

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

2112	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	No data available
Kerosine, petroleum (8008-20-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	18 g/m ³ /4h
Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg
Cumene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	>3160 mg/kg
LC50 inhalation rat	39000 mg/m ³ /4h
Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat	17.2 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	8390 mg/kg
LD50 dermal rat	12124 mg/kg
LC50 inhalation rat	28.1 mg/l/4h
Benzene (71-43-2)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	> 9.4 ml/kg
LC50 inhalation rat	13050-14380 ppm/4h
Furan (110-00-9)	
LC50 inhalation rat	3398 ppm/1h
Propylene oxide (75-56-9)	
LD50 oral rat	520 mg/kg
LD50 dermal rabbit	1244 mg/kg
LC50 inhalation rat	4000 ppm/4h
Acetaldehyde (75-07-0)	
LD50 oral rat	1930 mg/kg
LC50 inhalation rat	13300 ppm/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Benzene (71-43-2)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
	In OSHA Specifically Regulated Carcinogen list
Furan (110-00-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Propylene oxide (75-56-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
Acetaldehyde (75-07-0)	
IARC group	1 - Carcinogenic to humans (associated with consumption of alcoholic beverages), 2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

2112

Persistence and degradability : Not established.

12.3. Bioaccumulative potential

2112

Bioaccumulative potential : Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information	: Handle empty containers with care because residual vapors are flammable.

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 14: Transport information

In accordance with DOT

UN-No.(DOT) : UN1993
Proper Shipping Name (DOT) : Flammable liquids, n.o.s. (Petroleum, Benzene, 1,2,4-trimethyl-)
Department of Transportation (DOT) Hazard Classes : 3
Hazard labels (DOT) :



Packing group (DOT) : II

Additional information

Other information : No supplementary information available.
Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
Naphthalene (91-20-3)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %
Cumene (98-82-8)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %
Ethylbenzene (100-41-4)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	0.1 %
Toluene (108-88-3)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
Benzene (71-43-2)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	0.1 %
Furan (110-00-9)	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	0.1 %
Propylene oxide (75-56-9)	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 302 Threshold Planning Quantity (TPQ)	10000
SARA Section 313 - Emission Reporting	0.1 %

FVP FUEL INJECTOR CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Acetaldehyde (75-07-0)

Listed on United States SARA Section 313

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

SARA Section 313 - Emission Reporting

0.1 %

15.2. US State regulations

2112

State or local regulations

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

Indication of changes

: None.

Date of issue

: 12/31/2014

Other information

: None.

NFPA health hazard


: 2

NFPA fire hazard

: 3

NFPA reactivity

: 0



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : FVP INTAKE VALVE DEPOSIT CLEANER
CAS No : 2312

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel System cleaner.

1.3. Details of the supplier of the safety data sheet

Factory Motor parts
1380 Corporate Center Curve, #200
Eagan, MN 55121
866-387-3343

1.4. Emergency telephone number

Emergency number : (800) 373-6729
CHEMTREC (800) 424-9300
CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid 2
Acute toxicity 4 (Dermal, Inhalation)
Skin irritation 2
Carcinogenicity 2
Reproductive toxicity 2 (developmental)
Specific target organ toxicity - Repeated exposure 2
Aspiration hazard 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Highly flammable liquid and vapor. Harmful in contact with skin or if inhaled. Causes skin irritation. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces.– No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	60 - 100	Flam. Liq. 3 Acute Tox. 4 (Dermal, Inhalation) Skin Irrit. 2
Ethylbenzene	(CAS No) 100-41-4	7 - 30	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Carc. 2 Asp. Tox. 1
Toluene	(CAS No) 108-88-3	7 - 13	Flam. Liq. 2 Skin Irrit. 2 Repr. 2 STOT SE 3 STOT RE 2 Asp. Tox. 1
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	0.5 - 1.5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A Asp. Tox. 1
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Carc. 2 STOT SE 3 Asp. Tox. 1
Benzene	(CAS No) 71-43-2	< 0.1	Flam. Liq. 2 Acute Tox. 4 (Oral) Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1A STOT RE 1 Asp. Tox. 1
Naphthalene	(CAS No) 91-20-3	< 0.1	Acute Tox. 4 (Oral) Carc. 2
Furan	(CAS No) 110-00-9	< 0.1	Flam. Liq. 1 Acute Tox. 3 (Inhalation) Acute Tox. 4 (Oral) Skin Irrit. 2 Muta. 2 Carc. 1B STOT RE 2
Propylene oxide	(CAS No) 75-56-9	< 0.1	Flam. Liq. 1 Acute Tox. 3 (Inhalation) Acute Tox. 4 (Oral, Dermal) Eye Irrit. 2A Muta. 1B Carc. 2 STOT SE 3
Acetaldehyde	(CAS No) 75-07-0	< 0.1	Flam. Liq. 1 Eye Irrit. 2A Carc. 2 STOT SE 3

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Harmful in contact with skin. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not breathe gas/mist/vapors/spray. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, sparks, and flame.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Ethylbenzene (100-41-4)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	150 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Cumene (98-82-8)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

Benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	0.5 ppm
USA ACGIH	ACGIH STEL (ppm)	2.5 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (STEL) (ppm)	5 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	25 ppm

Naphthalene (91-20-3)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	50 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm

Furan (110-00-9)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

Propylene oxide (75-56-9)		
USA ACGIH	ACGIH TWA (ppm)	2 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Acetaldehyde (75-07-0)		
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	360 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: Clear.
Color	: Amber.
Odor	: Petroleum odor.
Odor threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: ~ 22 °C (~ 71 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapor pressure	: No data available.
Relative vapor density at 20 °C	: No data available.
Relative density	: 0.864 - 0.869
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Open flame.

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

10.5. Incompatible materials

Acids. Bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, aldehydes, hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful in contact with skin or if inhaled.

2312	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	>1000 but ≤2000 mg/kg
LC50 inhalation rat	>10.0 but ≤20.0 mg/l/4h (Calculated using ATE values)

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	> 1700 mg/kg
LC50 inhalation rat	5000 ppm/4 h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15354 mg/kg
LC50 inhalation rat	17.2 mg/l/4h

Toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	12124 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat	28.1 mg/l/4h

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	3400 ppm/4h
LC50 inhalation rat	> 5.2 mg/l/4h

Cumene (98-82-8)	
LD50 oral rat	1400 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	39000 mg/m ³ /4 h

Benzene (71-43-2)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	> 9.4 mL/kg
LC50 inhalation rat	13050 - 14380 ppm/4h

Naphthalene (91-20-3)	
LD50 oral rat	490 mg/kg
LD50 dermal rabbit	> 20 g/kg
LC50 inhalation rat	>340 mg/m ³ /4 h

Furan (110-00-9)	
LC50 inhalation rat	3398 ppm/1h

Propylene oxide (75-56-9)	
LD50 oral rat	520 mg/kg
LD50 dermal rabbit	1244 mg/kg
LC50 inhalation rat	4000 ppm/4h

Acetaldehyde (75-07-0)	
LD50 oral rat	1930 mg/kg
LC50 inhalation rat	13300 ppm/4h

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Suspected of causing cancer.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

Benzene (71-43-2)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
	In OSHA Specifically Regulated Carcinogen list

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen

Furan (110-00-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen

Propylene oxide (75-56-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen

Acetaldehyde (75-07-0)	
IARC group	1 - Carcinogenic to humans, 2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Suspected of damaging the unborn child.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Harmful if inhaled. May cause drowsiness, dizziness and central nervous system depression. May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	-------------------------------------------------------------------

12.2. Persistence and degradability

2312	
Persistence and degradability	Not established.

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.3. Bioaccumulative potential

2312

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available
Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No. : 3295

14.2. UN proper shipping name

Proper Shipping Name : Hydrocarbons, liquid, n.o.s. (Xylene, Ethylbenzene, Toluene)
Department of Transportation Hazard Classes : 3
Hazard labels :



Packing group : II

14.3. Additional information

Other information : No supplementary information available.
Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Ethylbenzene (100-41-4)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

Toluene (108-88-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Cumene (98-82-8)

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
--------------------------	----------------------------------------------------------------------------------------

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

FVP INTAKE VALVE DEPOSIT CLEANER

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Benzene (71-43-2)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting 0.1 %

Naphthalene (91-20-3)

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

SARA Section 313 - Emission Reporting 0.1 %

Furan (110-00-9)

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 302 Threshold Planning Quantity (TPQ) 500

SARA Section 313 - Emission Reporting 0.1 %

Propylene oxide (75-56-9)

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

SARA Section 302 Threshold Planning Quantity (TPQ) 10000

SARA Section 313 - Emission Reporting 0.1 %

Acetaldehyde (75-07-0)

Listed on SARA Section 313 (Specific toxic chemical listings)

EPA TSCA Regulatory Flag T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

SARA Section 313 - Emission Reporting 0.1 %


15.2. US State regulations

2312

State or local regulations This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

Indication of changes : None.
Date of issue : 07/24/2014
Other information : None.
NFPA health hazard : 2
NFPA fire hazard : 3
NFPA reactivity : 0



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product