

# FVP SYNTHETIC BLEND 15W-40 HEAVY DUTY MOTOR OIL



## HEAVY DUTY MOTOR OIL

FVP Synthetic Blend SAE 15W-40 Heavy Duty Motor Oil is formulated for use in high-speed four-stroke cycle diesel engines. This formula is designed to meet 2017 model year on-highway and Tier 4 non-road exhaust emission standards, as well as for previous model year diesel engines. This oil is formulated to use in all applications with diesel fuels ranging in sulfur content up to 500 ppm.

The premium synthetic-blend base oils used in FVP Synthetic Blend SAE 15W-40 Heavy Duty Motor Oil provide enhanced lubricity and cold-flow, and improved resistance to high-temperature degradation. The advanced additive package in this formulation reduces viscosity loss due to shear, and oil aeration. Also, the advanced, low-ash formulation provides protection against catalyst poisoning and particulate filter blocking, while preventing deposit formation and soot-related viscosity increase.

- Exceeds API CK-4/SN performance standards
- Formulated with synthetic-blend base stocks for improved resistance to thermal breakdown
- Optimum oxidation stability and volatility properties reduce oil consumption between services
- Advanced additive technology provides added resistance to sludge formation and piston deposits
- Carries API license for diesel (CK-4) and gasoline (SN)\*\* engine use
- Meets API Service Classification CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4, SN
- ACEA E11-2022, E7-2022, CAT ECF-3 & ECF-2, Cummins CES20086, CES20081, Detroit Diesel 93K222, 93K218, Ford WSS-M2C171, Mack EOS-4.5, EO-O Premium Plus, EO-N, MTU 2, Renault RLD-4, RLD-3, Volvo VDS-4.5, VDS-4, VDS-3

SAE GRADE	15W-40
Density @ 15°C, g/cm <sup>3</sup>	.870
Viscosity @ 40°C, cSt	110.5
Viscosity @ 100°C, cSt	14.8
Viscosity Index	139
Pour Point: °C (°F)	-48° (54)
Flash Point: °C (°F)	229 (444)
API Licensed Service:	CK-4/SN
Cold Cranking Simulator, cP	5,100 @ -20°C
TBN, mg KOH	10
Sulfated Ash, wt%	0.98

### PRODUCT SIZES

FVP15W40SB-QT	12/ case
FVP15W40SB-1GAL	3/ case
FVP15W40SB-5GAL	5 Gallon
FVP15W40SB-55GAL	55 Gallon



REACH FOR WHAT WORKS.™

[FVPparts.com](http://FVPparts.com) | 866.387.3343

FVP is a brand of Factory Motor Parts.



**FACTORYMOTORPARTS™**

WE SUPPLY YOUR SUCCESS.®