

FULL STRENGTH FORMULA MULTI-VEHICLE ANTIFREEZE/ COOLANT

FULL STRENGTH FORMULA

FVP® Full Strength Multi-Vehicle Antifreeze/Coolant is recommended, compatible, and formulated for use with any antifreeze/coolant in any vehicle with aluminum and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to guard against temperature extremes and ravages of rust, corrosion, and premature water pump failure. FVP® Full Strength Multi-Vehicle Antifreeze/Coolant provides extended life protection for cars and light-duty trucks up to 5 years or 150,000 miles* when added to any extended life coolant or when flushed and filled according to directions. Available in gallons and 55 gallon drums.

*- Compatible with other extended life and conventional coolants.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.



Product specifications when used as directed:

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/coolant of any make and model of automobile and light duty truck on the road, foreign or domestic
- May be added to any color antifreeze/coolant (color may change, but performance will not be affected)
- Protects aluminum and any other engine metals
- Free of phosphates, borates, nitrites, silicates and amines
- Universally works with all fluid colors; all OAT, POAT, HOAT & IAT

PRODUCT SIZES

FVPMV-GAL	1 gal.	6/case
FVPMV-55GAL	55 gal	drum



Composition by Volume

Ethylene Glycol
Soluble Inhibitors (Anhydrous)
Total Water
Dyes (Yellow)

Properties

Color
Odor

Ash Content - ASTM D 1119

pH - 50% by Volume Solution - ASTM D 1287

Reserve Alkalinity - ASTM D 1121

Specific Gravity

at 20/20°C - 50% by Volume Solution - ASTM D 1122

Freezing Point

40% by Volume Solution - ASTM D 1177

50% by Volume Solution - ASTM D 1177

60% by Volume Solution - ASTM D 1177

Boiling Point, under standard pressure

40% by Volume Solution - ASTM D 1120

50% by Volume Solution - ASTM D 1120

60% by Volume Solution - ASTM D 1120

Flash Point (Tag Open Cup) 70% by Volume Solution

Foam Test - ASTM D 1881

Average Net Weight/Gallon at 68°F (20°C)

Typical Values

94.6%
3.3%
2.1%
Trace

Yellow
Characteristic

.8%
8.8
1.6

1.0694

-12° F (-24 °C)
-34° F (-37° C)
-62° F (-52 °C)

223 °F (106 °C)
227 °F (108 °C)
232 °F (111 °C)

None
50 mL/2.2 sec
9.3 lbs.

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORYMOTORPARTS™

WE SUPPLY YOUR SUCCESS.®