

EXTENDED LIFE HEAVY DUTY GOLD ANTIFREEZE/ COOLANT



FULL STRENGTH FORMULA

FVP® Extended Life Heavy Duty Gold Antifreeze/Coolant is formulated for all heavy duty diesel trucks and passenger cars for top off or fill. Available in gallons and 55 gallon drums.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

Product specifications when used as directed:

- Advance corrosion protection
- Silicate and phosphate free, fully formulated nitrited organic acid technology
- 300,000 mile life formula

Formulated to satisfy:

- ASTM D6210, D3306, SAE J1941, SAE J1034, TMC RP329

Truck specifications:

- Caterpillar EC-1, Mack 14GS17004, Cummins CES 14603, Detroit Diesel 7SE29898 05

PRODUCT SIZES

CONCENTRATE

FVPHDGOLD-GAL 1 gal. 6/case
FVPHDGOLD-55GAL 55 gal drum

PREMIXED

FVP HDGOLD50/50-55G 55 gal. drum

Composition by Volume

Ethylene Glycol 90-95%
Soluble Inhibitors (Anhydrous) 2.2% min.
Total Water 2.8%
Dyes (Gold) Trace

Properties

Color

Gold

Odor

Characteristic

Ash Content - ASTM D 1119

2.5% max

pH - 50% by Volume Solution - ASTM D 1287

7.5 - 9.0

Reserve Alkalinity - ASTM D 1121

Concentrate

3 mL

50% mixture

1 mL

Specific Gravity

at 20/20°C - 50% by Volume Solution - ASTM D 1122

1.120 - 1.13

Freezing Point

40% by Volume Solution - ASTM D 1177

-10°F [-23°C]

50% by Volume Solution - ASTM D 1177

-34°F [-37°C]

60% by Volume Solution - ASTM D 1177

-62°F [-52°C]

Boiling Point†

40% by Volume Solution - ASTM D 1120

223°F [106°C]

50% by Volume Solution - ASTM D 1120

227°F [108°C]

60% by Volume Solution - ASTM D 1120

232°F [111°C]

Flash Point (Tag Open Cup) 70% by Volume Solution

None

Foam Test - ASTM D 1881

None

Average Net Weight/Gallon at 68°F [20°C] 50 ml/2 sec.

9 - 4 lbs.

† Atmospheric pressure



REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts.



FACTORY MOTOR PARTS™

WE SUPPLY YOUR SUCCESS.®