

# 50/50 PREDILUTED FORMULA MULTI-VEHICLE ANTIFREEZE/ COOLANT



## 50/50 PREDILUTED FORMULA

FVP® 50/50 Prediluted Multi-Vehicle Antifreeze/Coolant is recommended, compatible, and formulated for use with any antifreeze/coolant in any vehicle with aluminum and other engine metals. This formula has a concentrated blend of premium long-lasting inhibitors to guard against temperature extremes and ravages of rust, corrosion, and premature water pump failure. FVP® 50/50 Prediluted Multi-Vehicle Antifreeze/Coolant is a 50/50 blend of antifreeze/coolant concentrate and demineralized water that provides extended life protection for cars and light-duty trucks up to 5 years or 150,000 miles\* when added to any extended life coolant. Available in gallons and 55 gallon drums.

\*- Compatible with other extended life and conventional coolants.

- Always consult owner's manual to determine the specific maintenance, change over intervals for your vehicle.

### Product specifications when used as directed:

- Meets ASTM D 3306, D4985
- May be added to the antifreeze/coolant of any make and model of automobile and light duty truck on the road, foreign or domestic
- May be added to any color antifreeze/coolant (color may change, but performance will not be affected)
- Protects aluminum and any other engine metals

#### PRODUCT SIZES

FVPMV50/50-GAL	1 gal.	6/case
FVPMV50/50-DRUM	55 gal	drum



### Composition by Volume

Antifreeze/Coolant

Total Water

Dyes (Yellow)

**Properties**

**Color**

**Odor**

**Ash Content** - ASTM D 1119

**pH** - 50% by Volume Solution - ASTM D 1287

**Reserve Alkalinity** - ASTM D 1121

**Specific Gravity**

at 20/20°C - 50% by Volume Solution - ASTM D 1122

**Freezing Point**

50% by Volume Solution - ASTM D 1177

**Boiling Point, under standard pressure**

50% by Volume Solution - ASTM D 1120

**Flash Point** (Tag Open Cup) 70% by Volume Solution

**Foam Test** - ASTM D 1881

**Average Net Weight/Gallon** at 68°F (20°C)

### Typical Values

51%

49%

Trace

Yellow

Characteristic

.4% max

8.7

1.0

1.0694

-34°F (-37°C)

227°F (108°C)

None

50 ml/2.2 sec

8.9 lbs.

REACH FOR WHAT WORKS.™

FVPparts.com | 866.387.3343

FVP is a brand of Factory Motor Parts. ©Copyright 2019 Factory Motor Parts.



**FACTORYMOTORPARTS™**

WE SUPPLY YOUR SUCCESS.®