



The Confident Solution.™

15W-40 SYNTHETIC BLEND MOTOR OIL



FVP 15W-40 Synthetic Blend Motor Oil

is formulated to provide the highest level of equipment protection available. With the next generation of soot control FVP 15W-40 meets the latest API CJ-4/SM, Cummins® CES 20081, Volvo® VDS-4, Mack® EO-O Premium Plus (07), Caterpillar™ ECF-3, Renault RLD-3 and Detroit Diesel® Power Guard 93K218 standards. Especially designed for today's high-performance, low emissions diesel engine equipped with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filter. Available in quarts and gallons.

www.FVPparts.com • (866) 387-3343

15W-40 SYNTHETIC BLEND MOTOR OIL

FVP Synthetic Blend Motor Oil Typical Physical Properties	
SAE Grade	15W40
API Service	CJ-4/SM
API Gravity @ 60°F	29.90
Pour Point °C (°F)	-45 (-44)
Viscosity, cSt @ 40°C	124.3
Viscosity, cSt @ 100°C	15.5
Viscosity Index	140
Cold Crank, cSt @ -20	5800
Low-Temperature	18,700
Pumping (MRV), cSt @ -25	20,800
Noack Volatility	14.5
Neutralization No. (TBN_E)	11
1 Quart	Part # 15W40SB-QT
1 Gallon	Part # 15W40SB-1GAL

Minor variations in typical physical properties may occur from normal manufacturing processes

MEETS OR EXCEEDS THE FOLLOWING:

- API Service Classification CJ-4, CI-4 PLUS, CI-4, CH-4/SM
- API SM/SL/SJ for gasoline engines
- Mack EO-N Premium Plus '03, EO-M PLUS, EO-M
- Caterpillar ECF3 & ECF1
- Cummins CES 20081
- Global DHD-1
- Mercedes-Benz 228.3
- Volvo VDS-3 and VDS-4
- JASO DH-2
- MTU Type I & II